

DOOLITTLE TRAILER MFG.

UTILITY TRAILERS



Above The Rest



7712 77X12' (2,990 lbs GVWR) S/A Rail
shown with mesh gate and 2' high sides options

Key Points To Remember About Doolittle® Trailers

Standard Features

- New Tires
- Safety Chains
- Front Marker Lights (53 Series Option)
- Treated Yellow Pine Floor
- Pre-Wired Plug with Loom (Wiring Ran Through Punched Holes & Protected with Grommets)
- D.O.T. Lights
- Fabricated Fender with Double Gussets
- Painted with Rust Inhibiting Primer and Two Coats of Top Quality Acrylic Enamel
- White Spoke Wheels
- 2 3/8" Pipe Top Rail
- Stake Pockets

Popular Options

- 4' Mesh Ramp Gate
- High, Steel Sides
- Tilt Deck
- Fold Up Front Jack
- Spare Tire & Wheel
- Spare Tire Mount

See Page 5 For More Available Options



538 53X8 (1,500 lbs GVWR)
S/A Rail, tilt bed option

53 Series (1,500 lbs GVWR)

One Size: 53" Wide X 8'

Standard Equipment: 2x2 Square Tube Fabricated Tongue, Square Back Railing, Angle Iron Rail, 4 1/2" Tongue Grab Handle, 2" Coupler, 12" Tires



5610 56X10 S/A Rail (2,990 lbs GVWR)

56 Series (2,990 lbs GVWR)

56" Wide X Four Lengths: 8', 10', 12' & 14'

Standard Equipment: 3" Channel Tongue, 3-Pc, W/5000 LB Flip Up Set Back Jack - Bolted, 15" Tires

Utility S/A Rails

Single Axle Rail-style Transports

See checklist on page 5 for available options or visit us on line at www.doolittletrailers.com for a complete list of features and options.



6610 66X10 (2,990 lbs GVWR)
S/A Rail shown with mesh gate option.

66 Series (2,990 lbs GVWR)

66" Wide X Four Lengths: 8', 10', 12' & 14'

Standard Equipment: 3" Channel Tongue, 3-Pc, With Set Back 2000 LB Top Crank Jack - Bolted, 15" Tires

77 Series (2,990 lbs GVWR) not pictured

77" Wide X Three Lengths: 10', 12' & 14'

Standard Equipment: 3" Channel Tongue, 3-Pc, With Set Back 5000 LB Flip Up Top Crank Jack - Bolted, 15" Tires

SERIES	Width: Deck/Overall		Lengths Available: Deck/Overall	Gross Vehicular Weight Rating		Rail Height	Deck Height	Hitch Height	Hitch Size	Tire Size	Channel Tongue Size	Wheel Bolt/Pattern	Cross Member Spacing	Suspension Type
	Deck	Overall		lb	ft	ft	ft	ft	in	in	in	in	in	in
53	53"	69"	8'/11"2"	1,500 lbs	9"	15"	17"	2" Strt	4.8x12"	2x2 tube	5 /4.5"	24"	Slipper Spring	
56	56"	76"	8'/11"6"; 10'/13"6"; 12'/15"6"; 14'/17"6"	2,990 lbs	13"	17"	18"	2" AF	205-15"	3"	5 /4.5"	24"	Dbl Eye Spring	
66	66"	86"	8'/11"6"; 10'/13"6"; 12'/15"6"; 14'/17"6"	2,990 lbs	13"	17"	18"	2" AF	205-15"	3"	5 /4.5"	24"	Dbl Eye Spring	
77	77"	97"	10'/13"6"; 12'/15"6"; 14'/17"6"	2,990 lbs	13"	17"	18"	2" AF	205-15"	3"	5 /4.5"	24"	Dbl Eye Spring	

TM7716 77X16' (9,800 lbs GVWR)
T/A Rail shown with Heavy Duty Stand Up Ramps option



Utility T/A Rails

77 Series (7,000 lbs GVWR)

77" Wide X Five Lengths: 12', 14', 16', 18' & 20'

Standard Equipment: 4" Channel Tongue, 3-Pc, With Set Back 5000 LB Flip Up Top Crank Jack - Bolted, Electric Brake 1 Axle, 2 5/16" A-Frame Coupler, Breakaway with Battery Installed.

77 Series (9,800 lbs GVWR)

77" Wide X Five Lengths: 12', 14', 16', 18' & 20'

Standard Equipment: 3x5x1/4" Main Beams, 5" Channel Tongue, 3-Pc, With Set Back 5000 LB Flip Up Top Crank Jack - Bolted, Electric Brake 1 Axle, 2 5/16" A-Frame Coupler, Breakaway with Battery Installed.



T8216 82X16' (7,000 lbs GVWR) T/A Rail
shown with rear and side mesh gate, and 82" width options

SERIES	Width: Deck/Overall	Lengths Available: Deck/Overall	Gross Vehicular Weight Rating	Rail Height	Deck Height	Hitch Height	Hitch Size	Tire Size	Channel Tongue Size	Wheel Bolt/Pattern	Cross Member Spacing	Suspension Type	Angle Main Beams	Angle Uprights	Electric Brake Size
T7712	77"/95"	12'/15'6"	7,000 lbs	14"	17"	18"	2 ⁵ / ₁₆	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	2x3x3/16	2x2x3/16	2x10
T7714	77"/95"	14'/17'6"	7,000 lbs	14"	18.5"	18"	2 ⁵ / ₁₆	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	2x3x3/16	2x2x3/16	2x10
T7716	77"/95"	16'/19'6"	7,000 lbs	14"	18.5"	18"	2 ⁵ / ₁₆	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	2x3x3/16	2x2x3/16	2x10
T7718	77"/95"	18/21'6"	7,000 lbs	14"	18.5"	18"	2 ⁵ / ₁₆	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	2x3x3/16	2x2x3/16	2x10
T7720	77"/95"	20/23'6"	7,000 lbs	14"	18.5"	18"	2 ⁵ / ₁₆	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	3x4x1/4	2x3x3/16	2x10
TM7712	77"/95"	12/15'6"	9,800 lbs	16"	20"	19.5"	2 ⁵ / ₁₆	225-15"	5"	6 / 4.5"	12"	Dbl Eye Spring	3x5x1/4	2x3x3/16	2x12
TM7714	77"/95"	14/17'6"	9,800 lbs	16"	20"	19.5"	2 ⁵ / ₁₆	225-15"	5"	6 / 4.5"	12"	Dbl Eye Spring	3x5x1/4	2x3x3/16	2x12
TM7716	77"/95"	16/19'6"	9,800 lbs	16"	20"	19.5"	2 ⁵ / ₁₆	225-15"	5"	6 / 4.5"	12"	Dbl Eye Spring	3x5x1/4	2x3x3/16	2x12
TM7718	77"/95"	18/21'6"	9,800 lbs	16"	20"	19.5"	2 ⁵ / ₁₆	225-15"	5"	6 / 4.5"	12"	Dbl Eye Spring	3x5x1/4	2x3x3/16	2x12
TM7720	77"/95"	20/23'6"	9,800 lbs	16"	20"	19.5"	2 ⁵ / ₁₆	225-15"	5"	6 / 4.5"	12"	Dbl Eye Spring	3x5x1/4	2x3x3/16	2x12

Specifications and design subject to change without notification or obligation. Options may result in slight changes in specifications.

Doolittle Trailers are manufactured to Missouri's legal specifications. Check with your dealer about trailer laws in your state.



FTM7716 77x16 (9,800 lbs GVWR) T/A Flatbed
Shown with Heavy Duty Adjustable Ramps option

Utility T/A Flatbeds

Pull it on your next road trip.
Take it with you and be confident that you'll have a safe and trouble free road experience.

Also available in Single Axle sizes and GVWR.



FT7712 77x12 (7,000 lbs GVWR) T/A shown with mesh gate option.

SERIES	Width: Deck/Overall	Lengths Available: Deck/Overall	Gross Vehicular Weight Rating	Deck Height	Hitch Height Approx.	Hitch Size	Tire Size	Channel Tongue Size	Wheel/Bolt Pattern	Cross Member Spacing	Suspension Type	Angle Main Bennis	Elec. Brake Size
FT7712	77"/95"	12'/15'6"	7,000 lbs	18.5"	18"	2 5/16"	15"	4"	5/4.5	24"	Dbl Eye Sprg	3x5x1/4	2x10
FT7714	77"/95"	14'/17'6"	7,000 lbs	18.5"	18"	2 5/16"	15"	4"	5/4.5	24"	Dbl Eye Sprg	3x5x1/4	2x10
FT7716	77"/95"	16'/19'6"	7,000 lbs	18.5"	18"	2 5/16"	15"	4"	5/4.5	24"	Dbl Eye Sprg	3x5x1/4	2x10
FT7718	77"/95"	18'/21'6"	7,000 lbs	18.5"	18"	2 5/16"	15"	4"	5/4.5	24"	Dbl Eye Sprg	4x6x3/8	2x10
FT7720	77"/95"	18'/23'6"	7,000 lbs	18.5"	18"	2 5/16"	15"	4"	5/4.5	24"	Dbl Eye Sprg	4x6x3/8	2x10
FTM7712	77"/95"	12'/15'6"	9,800 lbs	20"	19.5"	2 5/16"	15"	5"	6 lug	16"	Dbl Eye Sprg	4x6x3/8	2x12
FTM7714	77"/95"	14'/17'6"	9,800 lbs	20"	19.5"	2 5/16"	15"	5"	6 lug	16"	Dbl Eye Sprg	4x6x3/8	2x12
FTM7716	77"/95"	16'/19'6"	9,800 lbs	20"	19.5"	2 5/16"	15"	5"	6 lug	16"	Dbl Eye Sprg	4x6x3/8	2x12
FTM7718	77"/95"	18'/21'6"	9,800 lbs	20"	19.5"	2 5/16"	15"	5"	6 lug	16"	Dbl Eye Sprg	4x6x3/8	2x12
FTM7720	77"/95"	20'/23'6"	9,800 lbs	20"	19.5"	2 5/16"	15"	5"	6 lug	16"	Dbl Eye Sprg	4x6x3/8	2x12
CH7716	77"/95"	16'/19'8"	7,000 lbs	18.5"	22"	2 5/16"	15"	4"	5/4.5	24"	Dbl Eye Sprg	3x5x1/4	2x10
CH7718	77"/95"	18'/21'8"	7,000 lbs	18.5"	22"	2 5/16"	15"	4"	5/4.5	24"	Dbl Eye Sprg	3x5x1/4	2x10

Specifications and design subject to change without notification or obligation. Options may result in slight changes in specifications.

Doolittle Trailers are manufactured to Missouri's legal specifications. Check with your dealer about trailer laws in your state.



CH8216 (7,000 lbs GVWR) 82X16' T/A Car Hauler Shown with optional Self Store Ramps and Tread Plate Runners

CH8216 (7,000 lbs GVWR) 82x16' T/A shown with Self Store Ramps and Tread Plate Runner options

Customized Utility

Whether you're hauling 4-wheelers or landscaping equipment, these rugged trailers are fully customizable and available with any of the popular add-on Doolittle features and packages.



T7716 77x16 (7,000 lbs GVWR) T/A Rail Shown with Landscaping and Mesh Gate options



6610 66x10' (2,990 lbs GVWR) S/A Rail Shown with 2' High Steel Sides, Dropped Down 3" for Easy Tie Down, Mesh Gate options.



Gooseneck Optional for all Utility Trailers

Options

UTILITY TRAILERS

- 4' or 5' Mesh Gate
- 4' or 5' Split Mesh Gate
- 5' Heavy Duty Self-Store Ramps
- 5' Heavy Duty Adjustable Ramps w/Legs
- Mesh Gate Over Heavy Duty Ramps
- 1/8" Diamond Plate Floor
- Wrap Tongue
- Flush Deck
- Adjustable Gooseneck
- Extra Wide 82" Deck
(Available on 77" wides only)
- Spare Tire
- Spare Tire Carrier
- Additional Tie Downs
- Double Electric Brakes
- Heavy Duty Diamond Plate Fenders
- Tear Drop Fenders
- Rear Three Bar Light
- Break-A-Way Switch w/Battery
(Standard on Tandem Axle Trailers)
- 2' Steel or Wood Dovetail
- Sealed Beam Lighting
- 2 5/16" Adjustable or Pintel Hitch
- Hydraulic Brakes
- Remote Wireless Brakes
- Weed Eater Racks
- High Sides
- Steel or Mesh Sides
- 2 5/16" Bulldog Coupler
- Double Crossmembers
- Thoroughly Painted Underneath



Spare Tire Mount & Tire



Heavy Duty D Ring



2' Dove Tail Shown with Optional Steel and Traction Bars, Heavy-duty Ramps with Spring Assist



Mesh Gate



Self-store Ramps with Safety Pin



Diamond Plate Floor



Mesh Gate, Over Heavy Duty Spring Assist Ramps




Adjustable Coupler

Standard Color: Black

Special Colors Available



Raven Black



Coke Red



Charcoal Gray

Above The Rest

SS66 66x10' (2,990 lbs GVWR)
S/A Steel Side shown with Green Paint
and 4' Mesh Gate options



Standard Equipment

- 3" Channel Tongue
- 3-Pc Tongue W/5000 LB Flip Up Set Back Jack - Bolted
- Tilt Bed
- 15" Tires
- D-Ring Tie Downs

SS series

SINGLE/TANDEM AXLE UTILITY

SERIES: Single/Tandem	Width: Deck/Overall *		Lengths Available: Deck/Overall	Gross Vehicular Weight Rating		Rail Height	Deck Height	Hitch Height	Hitch Size	Tire Size	Channel Tongue Size	Wheel Body/Pattern	Cross Member Spacing	Suspension Type
	Deck	Overall		Weight Rating	Weight Rating	Height	Height	Height	Size	Size	Size	Size	Spacing	Type
SS56	56"	76"	8'/11'6"; 10'/13'6"; 12'/15'6"; 14'/17'6"	2,990 lbs	13"	17"	18"	2" AF	205-15"	3"	5 / 4.5"	24"	Dbl Eye Spring	
SS66	66"	86"	8'/11'6"; 10'/13'6"; 12'/15'6"; 14'/17'6"	2,990 lbs	13"	17"	18"	2" AF	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	
SS77	77"	97"	10'/13'6"; 12'/15'6"; 14'/17'6"	2,990 lbs	13"	17"	18"	2" AF	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	
SST7714	77"	95"	14'/17'6"	7,000 lbs	14"	18.5"	18"	2 5/16"	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	
SST7716	77"	95"	16'/19'6"	7,000 lbs	14"	18.5"	18"	2 5/16"	205-15"	4"	5 / 4.5"	24"	Dbl Eye Spring	

*Also available in 82" Deck Widths

Specifications and design subject to change without notification or obligation. Options may result in slight changes in specifications.

Doolittle Trailers are manufactured to Missouri's legal specifications. Check with your dealer about trailer laws in your state.

Popular Option Packages

Single Axle Trailers

Basic Package S/A Trailers

- Mesh Gate
- Spare Tire & Wheel
- Spare Tire Mount

Deluxe Package S/A Trailers

- Self Store Ramps
- Spare Tire & Wheel
- Spare Tire Mount
- Fold Up Jack
- Two Additional D-Ring Tie Downs

Supreme Package S/A Trailers

- Mesh Gate
- Spare Tire & Wheel
- Spare Tire Mount
- Fold Up Jack
- Two Additional D-Ring Tie Downs

Tandem Axle Trailers

Basic Package T/A Trailers

- 5' Self Store Ramps
- Spare Tire & Wheel
- Spare Tire Mount

Deluxe Package T/A Trailers

- 5' Heavy Duty Self Store Ramps
- Spare Tire & Wheel
- Spare Tire Mount
- 82" Width Between Fenders (77 series only)
- Additional D-Ring Tie Downs

Supreme Package T/A Trailers

- 5' Heavy Duty Adjustable Ramps W/Legs
- Spare Tire & Wheel
- Spare Tire Mount
- 82" Width Between Fenders (77 series only)
- Additional D-Ring Tie Downs
- Wrap Tongue



A full line of replacement parts and options are available through our Doolittle Trailer parts Catalog. Contact your local dealer for more information.



Utilities In Stock

Above The Rest
Doolittle
 TRAILER MFG.
UTILITY TRAILERS
www.doolittletrailers.com



CARGO MASTER

DEALER QUOTE

ITEM	QTY	PRICE
TOTAL		

Call 1-800-654-4948 for the authorized Doolittle dealer nearest you.

[]

DEALER CONTACT INFORMATION

